



RO22169

Multi Protector Basic 2-Tone Jacket



Radio loop

Concealed
central YKK
zipVisible safety
standards

TICKING ALL BOXES

PROTECTION LEVEL:
ARC 2
10.2 cal/m²

Above shown is the ATPV value.

EN SAFETY STANDARDS



EN ISO 13688:2013

EN ISO 11611:2015
Class 2 A1 A2EN ISO 11612:2015
A1 A2 B1 C1 D0 E3 F1EN 61482-2:2020
APC 1
ELIM = 9,7 cal/m²
ATPV = 10,2 cal/m²EN 13034:2005 +
A1:2009
type 6ISO 15797:2002
75°CISO 6330:2012
60°C

QUICK DETAIL OVERVIEW

Available colours

Navy/Royal

Product code

RO22169

Sizing

UK38 - UK58

Fabric weight

Jacket: 320 g/m²

This garment is mostly used in > Petrochemicals

www.roots-original.com
Have questions? Email us at info@roots-original.com



RO22169

Multi Protector Basic 2-Tone Jacket

FEATURES & BENEFITS

- Central non-metallic YKK zip > With press studs at the top
- 2 Chest pockets with flap > Easy to access storage space
- 1 Radio/gas detector loop > Keep your instruments within reach
- 2 Front pockets with flap > Extra front storage space
- Pen pocket on left sleeve > Always keep a pen on you

KEY FEATURES



Treated FR fabric



Concealed non-metallic YKK zip



Triple stitched



Radio loop

Related products



RO22265 - Basic Trouser
Multi Protector Basic trousers

FABRIC INFORMATION

Fabric composition

FLC320 - 80% cotton / 19% polyester / 1% antistatic

Fabric weight

320 g/m²

FR Fabric Type

Treated

Additional certification



Logo

Certified for logo applications


1. Oeko-Tex Standard 100
2. AS/NZ 4399:1996 Sun protective clothing UPF 50+ (Excellent Protection)

Please visit www.roots-original.com/certificates to download all relevant certificates.

Product care instructions

To preserve the fabrics strength and protective capacity, we strongly advice to follow our detailed care instructions.

1. Always launder with coverall zippers closed.
2. Remove all tools from pockets
3. Rinse properly after wash.
4. Never wash flame retardant clothing with detergents containing bleach.
5. After washing, tumble dry at 50°C to avoid excessive shrinkage.
6. Do not iron directly over heat seal logos.



Whenever in doubt or in need of advice, ask your dry cleaner or contact us. We are here to help or visit www.roots-original.com/product-care



YOUR ARC FLASH PROTECTION SPECIALISTS

Get in contact, we'd love to help you!

Give us a call on +31 (0)10 2955 955 or drop us a message at: info@roots-original.com