



R022367

Multi Protector BiB



TICKING ALL BOXES

PROTECTION LEVEL:
ARC 2
10.2 cal/m²

Above shown is the ATPV value.

EN SAFETY STANDARDS


 EN ISO 13688:2013
 + A1:2021

 EN ISO 11611:2015
 A1 A2 Class 2
 (A1=50 washing cycles)

 EN ISO 11612:2015
 A1+A2 C1 D0 E3 F1
 (A1=50 washing cycles)

 EN 61482-2:2020
 ELIM 9,7 cal/cm2
 ATPV 10,2 cal/cm2
 APC 1 (4 kA)


ISO 6330 - 60°C



ISO 15797 - 75°C


 EN 13034:2005
 +A1:2009 Type 6

QUICK DETAIL OVERVIEW

Available colours

Grey/black

Product code

R022367

Sizing

UK36 - UK60

Fabric weight

BiB: 320 g/m²

Inside leg length

 Short: 29"
 Regular: 31"
 Tall: 33" (standard size)



RO22367

Multi Protector BiB

FEATURES & BENEFITS

Flame retardant retroreflective tape > Stay visible in any situation

Fly zip > Convenient central zip

2 Side pockets > Easy to access

Tool pocket and mobile phone pocket > Keep your gear in reach

2 Back pockets > With flap and velcro for extra security

Product is fit for domestic laundry > ISO 6330 - 60°C

Product is fit for industrial laundry > ISO 15797 - 75°C

KEY FEATURES



Treated FR fabric



Mobile phone pocket



Knee pad pockets



Fly zipper

Related products



RO8008 - ROOTS knee pads

A pair of foam knee pads



RO22167 - Multi protector jacket

Multi protector jacket

FABRIC INFORMATION

Fabric composition

FLC320- 80% cotton / 19% polyester / 1% antistatic

Fabric weight

320 g/m²

FR Fabric Type

Treated

Additional certification



1. Oeko-Tex Standard 100
2. AS/NZ 4399:1996 Sun protective clothing UPF 50+ (Excellent Protection)

Please visit www.roots-original.com/certificates to download all relevant certificates.


Logo

Certified for logo applications

Product care instructions

To preserve the fabrics strength and protective capacity, we strongly advice to follow our detailed care instructions.

1. Always launder with coverall zippers closed.
2. Remove all tools from pockets
3. Rinse properly after wash.
4. Never wash flame retardant clothing with detergents containing bleach.
5. After washing, tumble dry at 50°C to avoid excessive shrinkage.
6. Do not iron directly over heat seal logos.



Whenever in doubt or in need of advice, ask your dry cleaner or contact us. We are here to help or visit www.roots-original.com/product-care



YOUR ARC FLASH PROTECTION SPECIALISTS

Get in contact, we'd love to help you!

Give us a call on +31 (0)10 2955 955 or drop us a message at: info@roots-original.com