

right leg

# RO15390 **Kermel Nordic BiB**



# Refelctive elements

## **TICKING ALL BOXES**

PROTECTION LEVEL ARC 2
9.3 cal/m <sup>2</sup>
Above shown is the ATPV value

# **EN SAFETY STANDARDS**



EN 1149-5:2008



EN ISO 13688:2013

EN ISO 11611:2015 A1 A2 Class 2





EN ISO 11612:2015 A1 A2 B1 C1 D0 E0 F1

IEC 61482-2:2009 ATPV 9.3 cal/cm2 Class 1

EN 13034:2005 A1:2009 Type 6

### **QUICK DETAIL OVERVIEW**

#### Available colours

Navy Orange				
Product code		Sizing		
RO15390		UK36 - UK64		
Fabric weight		Inside leg length		
BiB:	230 g/m²	Short: Regular: Tall:	29" 31" 33" (standard size)	

This garment is mostly used in > Utilities / Petrochemicals / Renewables / Industrial electrical



# R015390 Kermel Nordic BiB

## **FEATURES & BENEFITS**

Flame retardant retroreflective tape > Stay visible in any situation
Large Chest pocket > Chest storage with easy access
2 Side swing pockets > With trouser access
2 Hip patch pockets > Easy to reach storage space
Rule pocket on right leg > Always space for a ruler
Knee pad pockets > Space for your knee pads

Garment fit for industrial laundry > Tested according ISO 15797

# **KEY FEATURES**



#### **Related products**



RO15190 - Kermel Nordic Jacket Kermel Nordic Jacket

# **FABRIC INFORMATION**

#### **Fabric composition**

Additional certification

**OEKO-TEX**®

STANDARD 100 🌺

SHWO 093194 TESTEX

AS/NZ 4399:1996 Sun protective clothing UPF 50+ (Excellent Protection)

Please visit www.roots-original.com/certificates to download all relevant certificates.

Oeko-Tex Standard 100

Kermel Alpha 4975 - 50% Kermel aramid / 25% Modacryl protex / 24% Tencel / 1% antistatic

#### Fabric weight

230 g/m<sup>2</sup>

2

# FR Fabric Type

Inherent

### Logo

Certified for logo applications

#### **Product care instructions**

To preserve the fabrics strength and protective capacity, we strongly advice to follow our detailed care instructions.

- 1. Always launder with coverall zippers closed.
- 2. Remove all tools from pockets
- 3. Rinse properly after wash.
- 4. Never wash flame retardant clothing with detergents containing bleach.
- 5. After washing, tumble dry at 50°C to avoid excessive shrinkage.
- 6. Do not iron directly over heat seal logos.

# \* 7H: @

Whenever in doubt or in need of advice, ask your dry cleaner or contact us. We are here to help or visit www.roots-original.com/product-care



# YOUR ARC FLASH PROTECTION SPECIALISTS

Get in contact, we'd love to help you!

Give us a call on +31 (0)10 2955 955 or drop us a message at: info@roots-original.com