



RO12085

Multi Protector Double Layer Arc Flash Coverall



Concealed non-metallic central YKK zipper



Visible safety standards



Triple stitched



Knee pad pockets

TICKING ALL BOXES

PROTECTION LEVEL:
ARC 3

26.8 cal/m²

Above shown is the ATPV value.

EN SAFETY STANDARDS



EN ISO 13688:2013



EN 1149-5:2018



EN ISO 11611:2015
Class 2 A1+A2



EN ISO 11612:2015
A1+A2 B1 C2 D0 E3 F1



IEC 61482-2:2018
ELIM 14.8 cal/cm²,
ATPV 26.8 cal/cm²,
APC 2 (7 kA)



EN 13034:2005
+A1:2009
Type 6

QUICK DETAIL OVERVIEW

Available colours

■ Royal

Product code

RO12085

Sizing

UK38 - UK54

Fabric weight

Coverall: 320g/m² + 185 g/m²

Inside leg length

Short: 29"
Regular: 31"
Tall: 33" (standard size)

This garment is mostly used in > Industrial electrical



RO12085

Multi Protector Double Layer Arc Flash Coverall

FEATURES & BENEFITS

- Extra high collar > Additional protection
- Concealed non-metallic central YKK zipper > Easy to open and close
- 2 Internal chest pockets > Stow away your goods
- 2 Large cargo pockets > Extra storage compartments
- 2 Side pockets > With easy trouser access
- Pen pocket on left sleeve > Tightly secure your knee pads
- Large knee pockets > Room for your knee pads

KEY FEATURES



Treated FR fabric



Knee pad pockets



Triple stitched



Visible safety standards



Concealed non-metallic central YKK zipper

FABRIC INFORMATION

Fabric composition

FLC320 + FLA185
80% cotton / 19% polyester / 1% antistatic

Fabric weight

320g/m² + 185 g/m²

FR Fabric Type

Treated

Additional certification



1. Oeko-Tex Standard 100
2. AS/NZ 4399:1996 Sun protective clothing UPF 50+ (Excellent Protection)

Please visit www.roots-original.com/certificates to download all relevant certificates.

Logo

Certified for logo applications

Product care instructions

To preserve the fabrics strength and protective capacity, we strongly advice to follow our detailed care instructions.

1. Always launder with coverall zippers closed.
2. Remove all tools from pockets
3. Rinse properly after wash.
4. Never wash flame retardant clothing with detergents containing bleach.
5. After washing, tumble dry at 50°C to avoid excessive shrinkage.
6. Do not iron directly over heat seal logos.



Whenever in doubt or in need of advice, ask your dry cleaner or contact us. We are here to help or visit www.roots-original.com/product-care



YOUR ARC FLASH PROTECTION SPECIALISTS

Get in contact, we'd love to help you!

Give us a call on +31 (0)10 2955 955 or drop us a message at: info@roots-original.com