



# RO12190HV Multi Protector Hi-Vis Jacket

## TICKING ALL BOXES

**PROTECTION LEVEL:**  
**ARC 2**  
**10.2 cal/cm<sup>2</sup>**

Above shown is the ATPV value.

## EN SAFETY STANDARDS



EN ISO 13688:2013



EN ISO 11611:2015  
A1 + A2 Class 2



EN ISO 11612:2015  
A1 A2 B1 C2 D0 E3 F1

IEC 61482-2:2009  
ATPV 10.2 cal/cm<sup>2</sup>  
Class 1



EN 13034:2005  
A1:2009 Type 6



EN ISO 20471:2013  
+A1:2016  
Class 2



## QUICK DETAIL OVERVIEW

### Available colours

 Hi-Vis Yellow/Navy  Hi-Vis Yellow/Red

### Product code

RO12190HV

### Sizing

UK38 - UK54

### Fabric weight

Jacket: 320 g/m<sup>2</sup>



# RO12190HV Multi Protector Hi-Vis Jacket

## FEATURES & BENEFITS

- Flame retardant retroreflective tape > Stay visible in any situation
- Concealed press stud closure > Sturdy and out of sight
- 2 chest pockets with flap and zip > Double the storage space
- Radio / gas detector loop above right pocket > Keep your instruments within reach
- 2 front pockets with flap > Double the storage within close reach
- Pen pocket on left sleeve > Always space for a pen

## KEY FEATURES



Treated FR fabric



2 chest pockets with flap and zip



Triple stitched



Radio / gas detector loop



Flame retardant retroreflective tape

## FABRIC INFORMATION

### Fabric composition

FLC320HV - 80% cotton / 19% polyester / 1% antistatic

### Fabric weight

320 g/m<sup>2</sup>

### FR Fabric Type

Treated

### Additional certification

### Logo

Certified for logo applications



1. Oeko-Tex Standard 100
2. AS/NZ 4399:1996 Sun protective clothing UPF 50+ (Excellent Protection)

Please visit [www.roots-original.com/certificates](http://www.roots-original.com/certificates) to download all relevant certificates.

### Product care instructions

To preserve the fabrics strength and protective capacity, we strongly advice to follow our detailed care instructions.

1. Always launder with coverall zippers closed.
2. Remove all tools from pockets
3. Rinse properly after wash.
4. Never wash flame retardant clothing with detergents containing bleach.
5. After washing, tumble dry at 50°C to avoid excessive shrinkage.
6. Do not iron directly over heat seal logos.



Whenever in doubt or in need of advice, ask your dry cleaner or contact us. We are here to help or visit [www.roots-original.com/product-care](http://www.roots-original.com/product-care)



## YOUR ARC FLASH PROTECTION SPECIALISTS

Get in contact, we'd love to help you!

Give us a call on +31 (0)10 2955 955 or drop us a message at: [info@roots-original.com](mailto:info@roots-original.com)