



RO2517

Stormbuster Xtreme Waterproof parka

TICKING ALL BOXES

PROTECTION LEVEL:
ARC 3

35.2 cal/m²

Above shown is the ATPV value.

EN SAFETY STANDARDS



Detachable
hood



EN ISO 13688:2013



EN ISO 11611:2015
A1 Class 2



EN ISO 11612:2015
A1 B1 C1 D0 E3 F1



IEC 61482-2:2009
ATPV 35.2 cal/cm²
Class 2



EN 13034:2005
A1:2009 Type 6



EN 343:2003
+ A1 2007 3/2



EN ISO 20471:2013
Class 3



Waterproof



Triple
stitched

QUICK DETAIL OVERVIEW

Available colours

 Hi-Vis Yellow/Navy

Product code

RO2517

Sizing

XS - 4XL

Fabric weight

Parka: 250 g/m² + 185 g/m²

This garment is mostly used in > Utilities / Petrochemicals / Renewables / Industrial Electrical



RO2517

Stormbuster Xtreme Waterproof parka

FEATURES & BENEFITS

Flame retardant retroreflective tape > Stay visible in any situation

Central zip with velcro closure > Easy to open and close

2 Napoleon pockets with zip > Double storage space

2 Front pockets with flap > More storage

Detachable hood > Swiftly transform your parka

Inner Pocket > Safely tuck away your goods

Two radio / gas detector loops > Keep your instruments within reach

KEY FEATURES



Detachable hood



2 Radio loops



High visibility



Inherent



Waterproof

FABRIC INFORMATION

Fabric composition

SBXWP + FLA185

60% modacrylic / 33% cotton / 5% nylon / 2% antistatic

Fabric weight

250 g/m² + 185 g/m²

FR Fabric Type

Inherent

Additional certification



1. Oeko-Tex Standard 100
2. AS/NZ 4399:1996 Sun protective clothing UPF 50+ (Excellent Protection)

Please visit www.roots-original.com/certificates to download all relevant certificates.

Logo

Certified for logo applications

Product care instructions

To preserve the fabrics strength and protective capacity, we strongly advice to follow our detailed care instructions.

1. Always launder with coverall zippers closed.
2. Remove all tools from pockets
3. Rinse properly after wash.
4. Never wash flame retardant clothing with detergents containing bleach.
5. After washing, tumble dry at 50°C to avoid excessive shrinkage.
6. Do not iron directly over heat seal logos.



Whenever in doubt or in need of advice, ask your dry cleaner or contact us. We are here to help or visit www.roots-original.com/product-care



YOUR ARC FLASH PROTECTION SPECIALISTS

Get in contact, we'd love to help you!

Give us a call on +31 (0)10 2955 955 or drop us a message at: info@roots-original.com