




RO23095LW

Flamebuster2 Lightweight Coverall



TICKING ALL BOXES

PROTECTION LEVEL:
ARC 2

10.1 cal/m²

Above shown is the ATPV value.

EN SAFETY STANDARDS



EN ISO 13688:2013



EN ISO 11612:2015
A1 B1 C1 D0 E0 F1
A1 = 50 washing cycles



EN 61482-2:2020
ELIM 9.2 cal/cm²
ATPV 10.1 cal/cm²
APC 1 (4 kA)



EN 13034:2005 +
A1:2009 Type 6



EN ISO 11611:2015
Class 1 A1

QUICK DETAIL OVERVIEW

Available colours

■ Navy ■ Red ■ Orange ■ Royal

Product code

RO23095LW

Sizing

UK36 - UK58
EU46 - EU68

Fabric weight

Coverall: 250 g/m²

Inside leg length

Short: 29"
Regular: 31"
Tall: 33" (standard size)

This garment is mostly used in > Offshore / Petrochemicals / Renewables

www.roots-original.com

Have questions? Email us at info@roots-original.com



RO23095LW

Flamebuster2 Lightweight Coverall

FEATURES & BENEFITS

Flame retardant retroreflective tape > Stay visible in any situation

Fully non-metallic > Virtually indestructible materials

Central YKK zipper > Easy to open and close

2 Chest pockets with YKK zip > Double storage space

2 Back pockets with flap > More storage

2 Side pockets with trouser access > Easy access

Rule pocket on right leg > Always space for a ruler

Pen pocket with flap on left sleeve > Keep a pen on you at all times

2 radio / gas detector loops > Keep your instruments within reach

KEY FEATURES



Treated fabric



2 Radio loops



Reflective elements



Triple stitched



Non metallic YKK zippers

FABRIC INFORMATION

Fabric composition

FB2 250 - 80% cotton / 19% polyester / 1% antistatic

Fabric weight

250 g/m²

FR Fabric Type

Treated

Additional certification



1. Oeko-Tex Standard 100
2. AS/NZ 4399:1996 Sun protective clothing UPF 50+ (Excellent Protection)

Please visit www.roots-original.com/certificates to download all relevant certificates.


Logo

Certified for logo applications

Product care instructions

To preserve the fabrics strength and protective capacity, we strongly advice to follow our detailed care instructions.

1. Always launder with coverall zippers closed.
2. Remove all tools from pockets
3. Rinse properly after wash.
4. Never wash flame retardant clothing with detergents containing bleach.
5. After washing, tumble dry at 50°C to avoid excessive shrinkage.
6. Do not iron directly over heat seal logos.



Whenever in doubt or in need of advice, ask your dry cleaner or contact us. We are here to help or visit www.roots-original.com/product-care



YOUR ARC FLASH PROTECTION SPECIALISTS

Get in contact, we'd love to help you!

Give us a call on +31 (0)10 2955 955 or drop us a message at: info@roots-original.com