



RO28090ULW

Flamebuster2 Nordic Ultra Light Weight Coverall



TICKING ALL BOXES

PROTECTION LEVEL:
ARC 1
5.4 cal/cm²

Above shown is the ATPV value.

EN SAFETY STANDARDS



EN ISO 13688:2013,



EN 1149-5:2018

EN 61482-2:2020
ELIM 4.6 cal/cm²,
ATPV 5.4 cal/cm²



EN ISO 11612:2015
A1+A2 B1 C1 D0 E0 F1

QUICK DETAIL OVERVIEW

Available colours

■ Navy ■ Red ■ Orange

Product code

RO28090ULW

Sizing

UK36 - UK64

Fabric weight

Coverall: 205 g/m²

Inside leg length

Short: 29"
Regular: 31"
Tall: 33" (standard size)

This garment is mostly used in > Offshore / Renewables / Petrochemicals

www.roots-original.com

Have questions? Email us at info@roots-original.com



RO28090ULW Flamebuster2 Nordic Ultra Light Weight Coverall

FEATURES & BENEFITS

Central zipper closure with press studs at the top > Easy to open and close

2 chest pockets with zip > Chest storage with easy access

2 back pockets > Double the storage space

2 side pockets with trouser access > Double leg storage with easy access

Rule pocket on right leg > Always space for a ruler

Pen pocket on left sleeve > Keep an easily reachable pen on you

KEY FEATURES



Treated FR fabric



Rule pocket



Triple stitched



Chest, back and side pockets



Central YKK zippers



Reflective elements



Lightweight

FABRIC INFORMATION

Fabric composition

99% cotton / 1% antistatic

Fabric weight

205 g/m²

FR Fabric Type

Treated

Additional certification

Logo

Certified for logo applications



1. Oeko-Tex Standard 100
2. AS/NZ 4399:1996 Sun protective clothing UPF 50+ (Excellent Protection)

Please visit www.roots-original.com/certificates to download all relevant certificates.

Product care instructions

To preserve the fabrics strength and protective capacity, we strongly advice to follow our detailed care instructions.

1. Always launder with coverall zippers closed.
2. Remove all tools from pockets
3. Rinse properly after wash.
4. Never wash flame retardant clothing with detergents containing bleach.
5. After washing, tumble dry at 50°C to avoid excessive shrinkage.
6. Do not iron directly over heat seal logos.



Whenever in doubt or in need of advice, ask your dry cleaner or contact us. We are here to help or visit www.roots-original.com/product-care



YOUR ARC FLASH PROTECTION SPECIALISTS

Get in contact, we'd love to help you!

Give us a call on +31 (0)10 2955 955 or drop us a message at: info@roots-original.com