



RO13020

Arcbuster Hot Worker Welding Coverall



No shoulder seams



Visible EN standards



Knee pad pockets

TICKING ALL BOXES

PROTECTION LEVEL:
ARC 2

18.0 cal/m²

Above shown is the ATPV value.

BODY BURN INJURY PREDICTION

2.7%

Body burn prediction of 2nd + 3rd degree burns.

EN SAFETY STANDARDS



EN 13688:2013



EN 1149-5:2018



EN ISO 11611:2015
Class 2 A1 A2




EN ISO 11612:2015
A1+A2 B1 C2 D0 E3 F1



EN 61482-2:2020
APC 1 (4 kA)
ELIM = 16,8 cal/m²
ATPV = 18,0 cal/m²

Body burn injury prediction



Burning wound

- No
- Pain (17,5%)
- 1st degree (0,9%)
- 2nd degree (1,8%)
- 3rd degree (0,9%)
- 2nd + 3rd degree burn: (2,7%)

Above shown body burn scores are without FR underwear.
Visit www.roots-original.com/burn-injury-predictions for more information.

QUICK DETAIL OVERVIEW

Available colours

- Navy
- Orange

Product code

RO13020

Sizing

UK36 - EU58

Fabric weight

Coverall: 440 g/m²

Inside leg length

Short: 29"
Regular: 31"
Tall: 33" (standard size)

This garment is mostly used in > Welding



RO13020

Arcbuster Hot Worker Welding Coverall

FEATURES & BENEFITS

- Concealed central non-metallic YKK zip > Behind double flap
- 1 Chest pocket with flap > Easy access storage space
- 1 Oversized chest pocket with flap > Extra storage
- 2 Back pockets with flap > Double storage space
- Toolbar above left chest pocket > Convenient space for tools
- 2 Rule pockets > Double storage space for rulers
- 2 Side pockets > Easy to reach storage compartments
- High collar with velcro > Extra neck protection
- Internal knee pockets > Stow away your knee pockets internally
- Possibility to zip on a welding hood > Swiftly transform your coverall

KEY FEATURES



Treated fabric



Visible EN standards



Possibility for shoulder pads



Triple stitched



Non metallic YKK central zip

Related products



RO13315 - Arcbuster Welders Hood
Detachable hood for welders coverall RO13020 and RO13310.

FABRIC INFORMATION

Fabric composition

FLC440 - 99% cotton / 1% antistatic

Fabric weight

440 g/m²

FR Fabric Type

Treated

Additional certification



1. Oeko-Tex Standard 100
2. AS/NZ 4399:1996 Sun protective clothing UPF 50+ (Excellent Protection)

Please visit www.roots-original.com/certificates to download all relevant certificates.

Logo

Certified for logo applications

Product care instructions

To preserve the fabrics strength and protective capacity, we strongly advice to follow our detailed care instructions.

1. Always launder with coverall zippers closed.
2. Remove all tools from pockets
3. Rinse properly after wash.
4. Never wash flame retardant clothing with detergents containing bleach.
5. After washing, tumble dry at 50°C to avoid excessive shrinkage.
6. Do not iron directly over heat seal logos.



Whenever in doubt or in need of advice, ask your dry cleaner or contact us. We are here to help or visit www.roots-original.com/product-care



YOUR ARC FLASH PROTECTION SPECIALISTS

Get in contact, we'd love to help you!

Give us a call on +31 (0)10 2955 955 or drop us a message at: info@roots-original.com