

RO22297 Multi Protector trousers



TICKING ALL BOXES

PROTECTION LEVEL ARC 2
10.2 cal/cm²

EN SAFETY STANDARDS



EN 1149-5:2018



EN ISO 13688:2013 + A1:2021

EN ISO 11611:2015 A1 A2 Class 2 (A1=50 washing cycles)

EN 13034:2005 +A1:2009 Type 6





EN ISO 11612:2015 A1 A2 B1 C2 D0 E3 F1 (A1=50 washing cycles)

ISO 15797 - 75°C





ISO 6330 - 60°C

QUICK DETAIL OVERVIEW

Available colours

Navy			
Product code		Sizing	
RO22297		UK28 - UK44	
Fabric weight		Inside leg length	
Trousers:	320 g/m²	Short: 29″ Regular: 31″	

Tall:

33" (standard size)

This garment is mostly used in > Renewables / Welding




R022297 Multi Protector trousers

FEATURES & BENEFITS

Elasticated waist > Adjust for the perfect fit Fly zip > Convenient central zip Tool loops left and right > Easily attach an external tool holder 2 Back pockets > With flaps and velcro for extra security 2 Cargo pockets > Convenient storage space on right and left leg Knee pad pockets > Space for your knee pads Product is fit for domestic laundry > ISO 6330 - 60°C Product is fit for industrial laundry > ISO 15797 - 75°C

KEY FEATURES



Related products



RO8008 - ROOTS knee pads A pair of foam knee pads

FABRIC INFORMATION

Fabric composition

Additional certification

AS/NZ 4399:1999 Sun protective clothing UPF 50+ (Excellent Protection)

OEKO-TEX®

Oeko-Tex Standard 100

STANDARD 100 SHWO 093194 TESTEX

FLC320-80% cotton / 19% polyester / 1% antistatic

Please visit www.roots-original.com/certificates to download all relevant certificates.

Fabric weight

320 g/m²

2

FR Fabric Type

Treated

Logo

Certified for logo applications

Product care instructions

To preserve the fabrics strength and protective capacity, we strongly advice to follow our detailed care instructions.

- 1. Always launder with coverall zippers closed.
- 2. Remove all tools from pockets
- 3. Rinse properly after wash.
- 4. Never wash flame retardant clothing with detergents containing bleach.
- 5. After washing, tumble dry at 50°C to avoid excessive shrinkage.
- 6. Do not iron directly over heat seal logos.





Whenever in doubt or in need of advice, ask your dry cleaner or contact us. We are here to help or visit www.roots-original.com/product-care



YOUR ARC FLASH PROTECTION SPECIALISTS

Get in contact, we'd love to help you!

Give us a call on +31 (0)10 2955 955 or drop us a message at: info@roots-original.com