



RO23160

Flamebuster2 Basic Jacket with limited chemical splash

TICKING ALL BOXES

PROTECTION LEVEL:
ARC 2

10.2 cal/cm²

Above shown is the ATPV value.

EN SAFETY STANDARDS



EN 340:2003



EN 1149-5:2008



EN ISO 11611:2015
A1 A2 Class 2
(A1=50 washing cycles)



EN ISO 11612:2015
A1 A2 B1 C2 D0 E3 F1
(A1=50 washing cycles)



IEC 61482-2:2009
ATPV 10.2 cal/cm²
Class 1



EN 13034:2005
+ A1:2009 Type 6



QUICK DETAIL OVERVIEW

Available colours

■ Navy ■ Red ■ Orange ■ Royal

Product code

RO23160

Sizing

UK36 - UK58

Fabric weight

Jacket: 320 g/m²

This garment is mostly used in > Petrochemicals / Renewables



RO23160

Flamebuster2 Basic Jacket with limited chemical splash

FEATURES & BENEFITS

Fully non-metallic > Durable non-metallic alternative. Virtually indestructible materials and more suited for laundry environments

Central zipper > Easy to open and close

2 Front pockets with velcro > Double the storage within close reach

2 Radio/gas detector loops > Keep your instruments within reach

Pen pocket on left sleeve > Keep an easily reachable pen on you

Possibility to place shoulder pads > Lessen the strain on the shoulders, extra comfort for scaffolders

KEY FEATURES



Treated FR fabric



2 front pockets with velcro



Central zipper



2 radio / gas detector loops



Possibility to place shoulder pads

Related products



RO23265 - Flamebuster2 Basic Trousers
Flamebuster2 Basic Trousers

FABRIC INFORMATION

Fabric composition

FLC320 - 80% cotton / 19% polyester / 1% antistatic

Fabric weight

320 g/m²

FR Fabric Type

Treated

Additional certification

Logo

Certified for logo applications



- Oeko-Tex Standard 100
- AS/NZ 4399:1996 Sun protective clothing UPF 50+ (Excellent Protection)

Please visit www.roots-original.com/certificates to download all relevant certificates.

Product care instructions

To preserve the fabrics strength and protective capacity, we strongly advice to follow our detailed care instructions.

- Always launder with coverall zippers closed.
- Remove all tools from pockets
- Rinse properly after wash.
- Never wash flame retardant clothing with detergents containing bleach.
- After washing, tumble dry at 50°C to avoid excessive shrinkage.
- Do not iron directly over heat seal logos.



Whenever in doubt or in need of advice, ask your dry cleaner or contact us. We are here to help or visit www.roots-original.com/product-care



YOUR ARC FLASH PROTECTION SPECIALISTS

Get in contact, we'd love to help you!

Give us a call on +31 (0)10 2955 955 or drop us a message at: info@roots-original.com