



RO18060

# Flamebuster Classic Basic Coverall

## TICKING ALL BOXES

**PROTECTION LEVEL:**  
**ARC 2**

**8.1 cal/m<sup>2</sup>**

Above shown is the ATPV value.

## EN SAFETY STANDARDS



IEC 61482-2:2009  
ATPV 8.1 cal/cm<sup>2</sup>  
Class 1



EN 1149-5:2008



EN ISO 11612:2008  
A1 B1 C1 D0 E0 F1



## QUICK DETAIL OVERVIEW

### Available colours

■ Navy ■ Red ■ Orange ■ Royal ■ Green

### Product code

RO18060

### Sizing

UK34 - UK60

### Fabric weight

Coverall: 350 g/m<sup>2</sup>

### Inside leg length

Short: 29"  
Regular: 31"  
Tall: 33" (standard size)

This garment is mostly used in > Offshore / Industrial electrical

[www.roots-original.com](http://www.roots-original.com)

Have questions? Email us at [info@roots-original.com](mailto:info@roots-original.com)



RO18060

# Flamebuster Classic Basic Coverall

## FEATURES & BENEFITS

- Flame retardant retroreflective tape > Stay visible in any situation
- Central zipper closure > With press studs at the top
- 2 Chest pockets > With zipper for a secure closure
- 2 Side pockets with trouser access > Double the storage space
- 2 Back pockets > Ambidextrous rear storage space
- Rule pocket on right leg > Always space for a ruler
- Pen pocket on the left sleeve > Always keep a pen on you

## KEY FEATURES



Treated FR fabric



Triple stitched



Rule pocket



2 Side pockets with trouser access

## FABRIC INFORMATION

### Fabric composition

FLC350 - 99% cotton / 1% antistatic

### Fabric weight

350 g/m<sup>2</sup>

### FR Fabric Type

Treated

### Additional certification



1. Oeko-Tex Standard 100
2. AS/NZ 4399:1996 Sun protective clothing UPF 50+ (Excellent Protection)

Please visit [www.roots-original.com/certificates](http://www.roots-original.com/certificates) to download all relevant certificates.

### Logo

Certified for logo applications

## Product care instructions

To preserve the fabrics strength and protective capacity, we strongly advice to follow our detailed care instructions.

1. Always launder with coverall zippers closed.
2. Remove all tools from pockets
3. Rinse properly after wash.
4. Never wash flame retardant clothing with detergents containing bleach.
5. After washing, tumble dry at 50°C to avoid excessive shrinkage.
6. Do not iron directly over heat seal logos.



Whenever in doubt or in need of advice, ask your dry cleaner or contact us. We are here to help or visit [www.roots-original.com/product-care](http://www.roots-original.com/product-care)



## YOUR ARC FLASH PROTECTION SPECIALISTS

Get in contact, we'd love to help you!

Give us a call on +31 (0)10 2955 955 or drop us a message at: [info@roots-original.com](mailto:info@roots-original.com)